



EN 14592/A1



www.montana.lu

Certificate

Circular smooth shank D-head nails for structural timber products

Diameter = 3.1mm Length = 63mm - 90mm

Properties of the material used:

- non alloy wire rod in accordance with EN 10016-1 to 4
- tensile strength in accordance with EN 10218-1, minimum 700 N/mm²

Characteristic mechanical properties:

- | | |
|--|---|
| - Yield moment: | $M_{y,k} = 5533 \text{ Nmm}$ |
| - Withdrawal strength parallel to grain:
Timber: minimum characteristic density of 310 kg/m ³ | $f_{ax,0,k} = 4.97 \text{ N/mm}^2$ |
| - Withdrawal strength perpendicular to grain:
Timber: minimum characteristic density of 310 kg/m ³ | $f_{ax,90,k} = 6.79 \text{ N/mm}^2$ |
| - Head pull-through parameter:
in OSB/3 with thickness $\geq 9 \text{ mm}$ | $f_{head,k} = 19.78 \text{ N/mm}^2$ |
| - Tensile capacity: | $f_{tens,k} = 4.96 \text{ kN}$ |

Durability (Corrosion Protection):

HDG (Hot Dipped Galv.) min 50 μ –
Service Class 3 acc. To EN1995-1-1

